

# FLASHINGS

<b>USE:</b>	Weather proofing metal roofing projects	
<b>QUALITIES:</b>	Apron and barge flashings, cappings, box guttering Made from Low tensile G300 Steel to assist cutting on site	
<b>DESIGN:</b>	Widths (Girth)	100mm – 1200mm
	Lengths	Made to order up to 8 metres
	Colours	all COLORBOND® colours & ZINCALUME®
<b>PROPERTIES:</b>	Zinc-aluminium alloy coated AZ150 conform to AS1397 Colour coated steel in accordance with AS2728 – Category 3	
	Tensile Strength (Minimum)	300 MPa
	Base Metal Thickness (BMT)	0.40mm & 0.55mm
	A plastic film protects this product from scratches during delivery and fixing	

## CUSTOM FLASHINGS - ORDERING PROCEDURE

ORDERING PROCEDURE	EXAMPLE
<ol style="list-style-type: none"> <li>1. Choose the appropriate profile type, material &amp; finish</li> <li>2. If colour, nominate the side on which colour is required</li> <li>3. Nominate dimensions by letters shown on the diagrams</li> <li>4. Nominate the angles on all bends</li> <li>5. Nominate the quantity and length of profile</li> </ol>	<ol style="list-style-type: none"> <li>1. Type 4, Colour Surfmist</li> <li>2. Colour on Side C</li> <li>3. A - 15mm B - 100mm C - 150mm D - 150mm</li> <li>4. CB = 90°, CD = 90°, AB = 65°</li> <li>5. 1 off, 2550mm</li> </ol>

Type 1 	Type 2 	Type 3 	Type 4 	Type 5 	Type 6 
Type 7 	Type 8 	Type 9 	Type 10 	Type 11 	Type 12 
Type 13 	Type 14 	Type 15 	Type 16 	Type 17 	Type 18 
Type 19 	Type 20 	Type 21 	Type 22 	Type 23 	Type 24 
Type 25 	Type 26 	Type 27 	Type 28 	Type 29 	Type 30 
Type 31 	Type 32 	Type 33 	Type 34 	Type 35 	SPECIAL 