



## QUAD 150 HIGH FRONT UNSLOTTED

- FOR RESIDENTIAL HOUSING IN HIGH RAINFALL REGIONS

### QUALITIES

- ✓ Unslotted to effect smooth lines
- ✓ High front designed to hide edge of roof sheets or tile edges
- ✓ Available in all COLORBOND® steel colours and ZINCALUME® steel

### INSTALLATION

Allow for gutter "fall" of at least 1 in 500 from the designated high points

<b>PANTEX FASCIA 185:</b>	Quad 150 High Front Gutter can be fixed to Pantex Metal Fascia 185 with spring clips, overstraps and overflow spacers*. Should be spaced every 900mm as a cluster.
<b>OTHER FASCIA</b>	Use internal gutter brackets spaced at 900mm for metal or timber fascia

Remove plastic coating from finished installation.

### ACCESSORIES

- Spring clips and Overstraps
- Internal gutter brackets
- 5mm Overflow spacers
- Stop ends - left and right hand
- Return ends - left and right hand
- Internal and External corners

### DESIGN

HEIGHT	98mm
WIDTH	150mm
LENGTHS	Custom up to 9.0m
EFFECTIVE CROSS SECTIONAL AREA (AS 2179)	7600mm <sup>2</sup>

### PROPERTIES

- ZINCALUME® steel alloy coated AZ150 conforms to AS1397
- COLORBOND® steel coated in accordance with AS2728 – Category 3

Base Metal Thickness BMT (mm)	-	0.42
Tensile Strength (MPa)	-	550
Mass (kg/lineal mtr) ZA	ZA	1.10
	CB	1.12
With Corestrip	ZA	No
	CB	Yes

### PERFORMANCE

- ✓ Designed to achieve gutter requirements in BCA 2016 Section 3.5.2
- ✓ Capable of carrying in excess of 40m<sup>2</sup> of roof area per downpipe in SE QLD\*

\*Refer to Gutter Overflow & Drainage Guidelines for overflow spacer requirements.