



QUAD 150 HIGH FRONT BIG SLOT

- FOR RESIDENTIAL HOUSING IN HIGH RAINFALL REGIONS

DESIGN

HEIGHT	98mm
WIDTH	150mm
LENGTHS	Custom up to 9.0m
EFFECTIVE CROSS SECTIONAL AREA (AS 2179)	6517mm ²

PROPERTIES

<ul style="list-style-type: none"> • ZINCALUME® steel alloy coated AZ150 conforms to AS1397 • COLORBOND® steel coated in accordance with AS2728 – Category 3 		
Base Metal Thickness BMT (mm)	-	0.42
Tensile Strength (MPa)	-	550
Mass (kg/lineal mtr)	ZA	1.10
	CB	1.12
With Corestrip	ZA	No
	CB	Yes

PERFORMANCE

- ✓ Designed to achieve gutter requirements in BCA 2016 Section 3.5.2
- ✓ Capable of carrying in excess of 40m² of roof area per downpipe in SE QLD*

QUALITIES

- ✓ Slotted to allow for excess water overflow volumes
- ✓ High front designed to hide edge of roof sheets or tile edges
- ✓ Available in all COLORBOND® steel colours and ZINCALUME® steel

INSTALLATION

Allow for gutter “fall” of at least 1 in 500 from the designated high points

PANTEX FASCIA 185:	Quad 150 High Front Gutter can be fixed to Pantex Metal Fascia 185 with spring clips, overstraps and overflow spacers*. Should be spaced every 900mm as a cluster.
OTHER FASCIA	Use internal gutter brackets spaced at 900mm for metal or timber fascia

Remove plastic coating from finished installation.

*Refer to Gutter Overflow & Drainage Guidelines for overflow spacer requirements.

ACCESSORIES

- Spring Clips
- Internal Gutter Brackets
- Stop Ends
- Internal & External Corners
- Overstraps
- 5mm Overflow Spacers
- Return Ends